

## Model : AEM-560 Electro Magnetic Lock



### Technical Specifications : (Fail Safe Lock) No Power unlock

<b>Model :</b>	AEM560
<b>Dimensions:</b>	250L x 42W x 25H (mm)
<b>Armature Plate:</b>	180L x 38W x 11H (mm)
<b>Holding Force:</b>	280kgs (600Lbs)
<b>Voltage:</b>	12/24VDC $\pm$ 10% Fail Safe No Power Lock Release
<b>Current Draw:</b>	12V/500mA, 24V/250mA
<b>Suitable For:</b>	Wooden Door, Glass Door, Metal Door, Fireproof Door
<b>Door Status Sensor:</b>	(NO/ NC/ COM)
<b>LED Indication:</b>	Green – Door Lock ; Red – Door Unlock
<b>Surface Temp:</b>	$\leq$ +20°C
<b>Operating Temp:</b>	10 ~ +55°C (14-131F)
<b>Suitable Humidity:</b>	0~90% (Non-condensing)
<b>Material For Shell:</b>	Anodized Aluminium
<b>Material For Magnetic:</b>	Zinc
<b>Material For Armature:</b>	Zinc
<b>Weight:</b>	2kgs
<b>Open Mode:</b>	90 Degree swinging door (One Way)
<b>Optional Bracket:</b>	LBK-560U, LBK560L, LBK-560Z
<b>Country of origin</b>	China